

The Torrent

Industrial Hard Surface Cleaner

Tor-rent (tôr'ent) - A violently fast stream of water (or other liquid). "The tile and grout was cleaned by a torrent of water".

When cleaning tile and grout, you need a machine that can stand up to long hours and demanding environments. The Torrent has been specifically engineered for just such environments. Equipped with an HT Technology Triplex Plunger Pump, the Torrent can withstand water temperatures up to 185° F and needs no standard service until 3,000 hours. This industrial strength pump has run-dry-seal capability and is adjustable from 400-1200 psi, giving the operator the versatility and power they need to get the job done efficiently and effectively. Direct water feed increases production by eliminating the need to stop working and fill a solution tank. Automatic dump out keeps the recovery tank empty at 2.5 gallons per minute through a standard 3/4" garden hose, also increasing production. Other innovations included the dual, top-mounted three-stage vacuums that have increased airflow efficiency and dramatically increased water recovery. This means floors will dry quicker and rooms can be put back into use with minimal downtime. With a new upright, ergonomic, lightweight design, the Torrent is easy to transport or store by a single person. Large rear wheels and skid bars allow the operator easy travel up or down stairs. Other industrial strength features include the rotationally molded body and comes standard with a lifetime warranty against cracks, dents, and leaks. Additional value added features are the smart circuit locator, amp gauge, wand caddy, hour meter, and multiple stage filtration system.

The Torrent will help increase your productivity and cleaning effectiveness, contact us today to find out more about this innovative industrial hard surface machine.



The Torrent

Industrial Hard Surface Cleaner

SPECIFICATIONS:

- Dimensions – 25"W x 26"L x 40"T
- Weight – 145 lbs.
- 2500 psi (Fully adjustable 1200 – 400 psi working pressures) HT Technology Triplex Plunger Pump
 - High Temperature/Run Dry Seal Capability (185 Deg. F.)
 - Extended Service Intervals (up to 3,000 hours)
 - Direct water feed reduces cavitation and possible pump damage, inline filter prevents debris from damaging system
 - Pressure gauge and amp gauge provided for proper pressure adjustment
- Premium Efficiency "Wattsaver" Totally Enclosed Fan Cooled Motor
 - 1200 psi @ 2.1 gpm under 15 amps
 - Best class (F) motor windings for longer life
- Vacuum – Twin 3-Stage top/parallel mounted "High Flow System"
 - Parallel mounted for high cfm
 - Unique "Air Horn" vacuum manifold for high efficiency
 - Exhaust diffuser reduces db's for quieter operation
- Auto Dump pump – 2.5 gpm continuous operation (Float Controlled)
- 10" wheels positioned to climb stairs. Rear wheels and top of handle form "Skid Rails" for ease of loading
- Filtration System – Pre-Filter – 800 micron polyester mesh with quick change feature, stainless steel 50 mesh tank filter
- Smart Circuit Locator – Locates two separate circuits to eliminate blown fuses or tripped circuit breakers
- Power Cords - Two 25', 12 gauge, 3-wire hospital grade plugs
- Power Consumption - 15 amps per cord
- Hour meter
- Wand caddy designed for Turbo tool - Part # HFT-40
- 1 1/2" x 25' vacuum and 25' high pressure hose included
- 50' long x 3/4" diameter Direct water feed hose, chemical injection, regulator and back flow prevention included.



Optional Turbo
Hard Surface Tool
Part Number HFT-40



Optional Mini Turbo
Hard Surface Hand
Tool Part # HFT-43



181 W. Aqua Avenue
Coeur d'Alene, ID 83815
Phone: (208) 772-0573
Toll Free: (800) 257-7982
Fax: (208) 772-0577
Web: www.usproducts.com

U.S. PRODUCTS

Quality made in the USA

Industrial Hard Surface Cleaner